

LOWEST COST

# Dyna-Blue<sup>®</sup>

Heavy Duty Cable Lubricant



*With Clingability*



- Clean-Easy to use
- Stays slippery-  
Won't dry out
- Lower cost

- Temperature stable-  
No waste
- Safe-Use with all cables
- UL listed

# Dyna-Blue® Cable Lubricant

Dyna-Blue® Lubricant is a clean, slow-drying, and easy to apply gel lubricant. It is a thick gel with “clingability” for easy handling and application. Dyna-Blue® combines effectiveness with economy. It is a good lubricant for everyday use in general electrical applications.

Dyna-Blue® Lubricant is harmless to humans, environmentally safe, compatible with cable jacket materials and exceptionally easy to work with. Dyna-Blue® is UL listed.

Package Size	Dyna-Blue® Product Number
55-gallon drum (208 Liter)	<b>D-Drum</b>
5-gallon pail (18.9 Liter)	<b>D-640</b>
1-gallon pail (3.78 Liter) 4/case	<b>D-128</b>
1-quart squeeze bottle (.95 Liter) 12/case	<b>D-35</b>

## Specifications

- Lubricity:** PVC or XLP-jacketed cable on PVC conduit at 200 lbs/ft (2.9 kN/m) normal pressure; coefficient of dynamic friction <.15.  
PVC or XLP-jacketed cable on EMT conduit at 200 lbs/ft (2.9 kN/m) normal pressure; coefficient of dynamic friction <.15
- Percent Non-Volatile Solids:** 3.5%
- Appearance:** Thick, light-blue gel material
- Wax, Grease and Silicone Content:** None
- Temperature Use Range:** 20°F - 140°F (-5°C - 60°C)
- pH:** 6.5 to 8.5
- Cable Compatibility:** No deleterious effects on physical or electrical properties of cable jackets.
- Polyethylene Stress Cracking:**  
No stress cracking on LDPE cable jacket when tested by ASTM D1693.
- Cling Factor:** 12 inches (30 cm) of a 1 inch (2.5 cm) diameter cable will hold at least 75 grams of lubricant for one minute when held vertically (at 70°F/20°C)
- Temperature Stability:** No more than 10% change in Brookfield viscosity from 40°F to 100°F (5°C to 38°C). No phase-out after five freeze/thaw cycles or 24-hour exposure at 120°F (50°C).
- Toxicity:** Non-toxic and non-sensitizing. Industrial use only
- Cleanup:** Complete cleanup possible with water.
- Flammability:** Lubricant has no flash point and dried residue is non-flammable.

View this flyer and its MSDS online at: <http://www.polywater.com/dynablue.html>

Copyright © 1998-2002. American Polywater Corporation. All Rights Reserved

Important Notice: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from product's use, regardless of the legal theory asserted.

Lit – Dflyer/9-02/MPS (9/02)



custserv@polywater.com(e-mail)  
<http://www.polywater.com>(URL)

P.O. Box 53  
Stillwater, MN 55082  
U.S.A.

1-800-328-9384  
1-651-430-2270  
fax 1-651-430-363