







COMPONENTS AND ACCESSORIES

TERMINATION KITS



Product name	Order reference	Description
Pyropak kit w/ mastic compound 	Refer to data sheet H58421 or contact Pentair Thermal Management for order reference number	Mastic compound Pyropak termination kit contains all material necessary to terminate two MI cable ends in nonhazardous or hazardous locations (see data sheet H58421). Available with 12" (300 mm) or 36" (900 mm) tails.
Pyropak kit w/ epoxy resin seal 	Refer to data sheet H58421 or contact Pentair Thermal Management for order reference number	Epoxy resin Pyropak termination kit contains all material necessary to terminate two MI cable ends in nonhazardous and hazardous locations (see data sheet H58421). Available with 12" (300 mm) or 36" (900 mm) tails.
QuickTerm kit 	Refer to data sheet H58421 or contact Pentair Thermal Management for order reference number	QuickTerm termination kits use a self-amalgamating tape and contain all the material necessary to terminate two ends of #6 AWG and larger single conductor copper-sheathed MI cable.

COMPONENTS



Product name	Order reference	Description
PVC shrouds 	SHRD1/2 SHRD3/4 SHRD1	Recommended for polymer-jacketed copper-sheathed MI cables, PVC shrouds are used to protect the brass gland connector from corrosion. PVC shroud for 1/2" gland PVC shroud for 3/4" gland PVC shroud for 1" gland

COMPONENTS AND ACCESSORIES


COMPONENTS

Product name	Order reference	Description
Splice 	Refer to data sheet H58429 or contact Pentair Thermal Management for order reference number	Splices are used to extend the nominal coil length where longer runs are required. Available for fire-rated and non-fire-rated cables. Factory-installed splices. Available for fire-rated applications. Field-installed splices for non-fire-rated applications
Field fire - protection kit 	STJFPR012 STJFPR034 STJFPR01 STJFPR0114	Thermal barrier system for fire protection of a field-installed splice for copper-sheathed MI cables. One kit is required for each field-installed splice. For use with a field-installed splice utilizing 1/2" gland For use with a field-installed splice utilizing 3/4" gland For use with a field-installed splice utilizing 1" gland For use with a field-installed splice utilizing 1-1/4" gland


ACCESSORIES

Product name	Order reference	Cable diameter	Description				
One-hole clips 			A	B	C	D	E
	CLIP196	0.196 - 0.215"	0.200"	5/16"	0.028"	5/32"	3/16"
	CLIP216	0.216 - 0.235"	0.220"	"	"	"	"
	CLIP236	0.236 - 0.255"	0.240"	"	"	"	"
	CLIP256	0.256 - 0.275"	0.260"	"	"	"	"
	CLIP276	0.276 - 0.295"	0.280"	"	"	"	"
	CLIP296	0.296 - 0.315"	0.300"	3/8"	"	13/64"	7/32"
	CLIP316	0.316 - 0.335"	0.320"	"	"	"	"
	CLIP336	0.336 - 0.365"	0.340"	"	"	"	"
	CLIP366	0.366 - 0.395"	0.370"	"	"	"	"
	CLIP396	0.396 - 0.425"	0.400"	"	"	"	"
	CLIP426	0.426 - 0.465"	0.430"	"	"	"	"
	CLIP466	0.466 - 0.505"	0.470"	"	"	"	"
	CLIP506	0.506 - 0.535"	0.510"	1/2"	0.047"	7/32"	1/4"
	CLIP536	0.536 - 0.585"	0.540"	"	"	"	"
	CLIP585	0.586 - 0.625"	0.590"	"	"	"	"
	CLIP626	0.626 - 0.665"	0.630"	"	"	"	"
	CLIP666	0.666 - 0.705"	0.670"	5/8"	0.055"	9/32"	5/16"
	CLIP706	0.706 - 0.745"	0.710"	"	"	"	"
	CLIP746	0.746 - 0.785"	0.750"	"	"	"	"

ACCESSORIES

Product name	Order reference	Cable diameter	Description						
Two-way straps			Straps to secure two copper-sheathed MI cables directly to mounting surface. For cables up to 0.75" in diameter. Material - copper.						
	2STP210	0.210 - 0.225"	0.207"	0.469"	1-1/16"	1-7/16"	5/32"	5/16"	0.028"
	2STP226	0.226 - 0.246"	0.226"	0.508"	"	"	"	"	"
	2STP247	0.247 - 0.277"	0.246"	0.571"	"	"	"	"	"
	2STP278	0.278 - 0.309"	0.274"	0.634"	"	"	"	"	"
	2STP310	0.310 - 0.345"	0.305"	0.713"	1-13/32"	1-53/64"	13/64"	3/8"	"
	2STP346	0.346 - 0.387"	0.344"	0.795"	"	"	"	"	"
	2STP388	0.388 - 0.434"	0.384"	0.874"	"	"	"	"	"
	2STP435	0.435 - 0.465"	0.423"	0.953"	1-29/32"	2-7/16"	7/32"	1/2"	0.047"
	2STP466	0.466 - 0.512"	0.467"	1.035"	"	"	"	"	"
	2STP513	0.513 - 0.545"	0.506"	1.114"	"	"	"	"	"
	2STP546	0.546 - 0.590"	0.545"	1.201"	"	"	"	"	"
	2STP591	0.591 - 0.637"	0.589"	1.299"	"	"	"	"	"
	2STP638	0.638 - 0.700"	0.636"	1.417"	2-13/32"	3-3/64"	9/32"	5/8"	0.055"
	2STP701	0.701 - 0.755"	0.699"	1.543"	"	"	"	"	"


ACCESSORIES

Product name	Order reference	Description
Support bracket and hanger		
	BRACK	The bracket is used to support single conductor copper-sheathed MI cables banded together in triplex and quadruplex. Use with MI cable sizes 1/0 AWG and smaller.
	HANG	The hanger is used with the support bracket to temporarily hold the MI cables as they are being banded together.

Adjustable banding




	WPS-01	Adjustable, easy-release pipe straps used to band MI cables in triplex or quadruplex. For 0.275" to 0.621" OD cable
	WPS-03	For 0.684" to 1.0" OD cable

Banding kit

	BANKIT	Stainless steel banding and clips used to band MI cables together. Complete with 50 ft of strapping (1/2" wide x 0.020" thick) and 75 clips.
---	--------	--

COMPONENTS AND ACCESSORIES

ACCESSORIES

Product name	Order reference	Description																														
Brass plates 	See table	Brass plates are used to avoid induction heating of ferrous metal enclosures where single conductor cables pass through the wall of the enclosure. Custom sizes available. Brass Plate Ordering Information <table><tr><th></th><th colspan="4">Number of holes</th></tr><tr><th>Hole size</th><th>3 hole</th><th>4 hole</th><th>5 hole</th><th>6 hole</th></tr><tr><td>1/2"</td><td>3H01/2</td><td>4H01/2</td><td>5BP12</td><td>6BP12</td></tr><tr><td>3/4"</td><td>3H03/4</td><td>4H03/4</td><td>5BP34</td><td>6H03/4</td></tr><tr><td>1"</td><td>3H01</td><td>4H01</td><td>5BP1</td><td>6H01</td></tr><tr><td>1-1/4"</td><td>3H01-1/4</td><td>4H01-1/4</td><td>5BP114</td><td>6H01-1/4</td></tr></table>		Number of holes				Hole size	3 hole	4 hole	5 hole	6 hole	1/2"	3H01/2	4H01/2	5BP12	6BP12	3/4"	3H03/4	4H03/4	5BP34	6H03/4	1"	3H01	4H01	5BP1	6H01	1-1/4"	3H01-1/4	4H01-1/4	5BP114	6H01-1/4
	Number of holes																															
Hole size	3 hole	4 hole	5 hole	6 hole																												
1/2"	3H01/2	4H01/2	5BP12	6BP12																												
3/4"	3H03/4	4H03/4	5BP34	6H03/4																												
1"	3H01	4H01	5BP1	6H01																												
1-1/4"	3H01-1/4	4H01-1/4	5BP114	6H01-1/4																												
Mastic sealing compound 	COMGRN4	Used to seal MI cable ends for nonhazardous and hazardous locations. Mastic compound does not require curing. Ten pieces per package.																														
Standard epoxy resin sealing compound	EPOXIPAC	Used to seal MI cable ends for nonhazardous and hazardous locations. Maximum temperature 248°F (120°C). Order additional 13.3 ml 2-part epoxy packs as required (see table below).																														
Optional epoxy resin sealing compound 	DURACOM	Used to seal MI cable ends for nonhazardous and hazardous locations. Maximum temperature 392°F (200°C). Order additional 13.3 ml 2-part epoxy packs as required (see table below). Two-Part Epoxy Requirements <table><tr><th>Gland size</th><th>1 pot</th><th>2 pots</th><th>3 pots</th><th>4 pots</th></tr><tr><td>1/2"</td><td>1</td><td>1</td><td>1</td><td>2</td></tr><tr><td>3/4"</td><td>1</td><td>2</td><td>3</td><td>4</td></tr><tr><td>1"</td><td>2</td><td>3</td><td>5</td><td>6</td></tr><tr><td>1-1/4"</td><td>2</td><td>4</td><td>5</td><td>7</td></tr></table>	Gland size	1 pot	2 pots	3 pots	4 pots	1/2"	1	1	1	2	3/4"	1	2	3	4	1"	2	3	5	6	1-1/4"	2	4	5	7					
Gland size	1 pot	2 pots	3 pots	4 pots																												
1/2"	1	1	1	2																												
3/4"	1	2	3	4																												
1"	2	3	5	6																												
1-1/4"	2	4	5	7																												



WWW.THERMAL.PENTAIR.COM

NORTH AMERICA

Tel: +1.800.545.6258
Fax: +1.800.527.5703
Tel: +1.650.216.1526
Fax: +1.650.474.7711
thermal.info@pentair.com

EUROPE, MIDDLE EAST, AFRICA

Tel: +32.16.213.511
Fax: +32.16.213.603
thermal.info@pentair.com

ASIA PACIFIC

Tel: +86.21.2412.1688
Fax: +86.21.5426.2917
cn.thermal.info@pentair.com

LATIN AMERICA

Tel: +55.11.2588.1400
Fax: +55.11.2588.1410
thermal.info@pentair.com

Pentair, Pyrotenax, PyroPak, and QuickTerm are owned by Pentair or its global affiliates. All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice..

© 2005–2013 Pentair.